

ステンレス熱間チャンネル

SUS304, SUS316, SUS316L

(単位:mm)

サイズ					Kg/P			r1	r2	断面積 (a) (cm ²)	重心の 位置 (cm)		断面二次 モーメント(i) (cm ⁴)		断面二次 半径(i) (cm)		断面係数 (Z) (cm ³)	
					SUS304		SUS316 SUS316L				Cx	Cy	Ix	Iy	ix	iy	Zx	Zy
t	x	B	x	H	4,000	6,000	6,000											
3	x	20	x	40		10.8		4	2	2.271	0	0.59	5.22	0.778	1.52	0.585	2.61	0.552
3	x	25	x	50		13.7		4	2	2.871	0	0.72	10.6	1.60	1.92	0.746	4.26	0.895
3	x	40	x	80		22.3		4.5	2	4.69	0	1.09	46.6	7.07	3.15	1.23	11.6	2.43
3	x	50	x	100		28.5	●	6.5	2	5.990	0	1.32	94.7	14.2	3.98	1.54	18.9	3.86
4	x	50	x	100	24.8	37.2	37.4	6.5	3	7.823	0	1.36	121.0	18.2	3.93	1.52	24.2	4.99
5	x	40	x	80	24.0	35.9	36.1	4.5	3	7.548	0	1.16	71.1	10.9	3.07	1.20	17.8	3.83
5	x	50	x	100	30.6	45.9	46.2	6.5	3	9.643	0	1.40	146.0	22.1	3.89	1.52	29.2	6.16
6	x	50	x	100	36.1	54.1	54.4	6.5	4.5	11.37	0	1.43	168.0	25.3	3.85	1.49	33.7	7.09
6	x	60	x	120		65.4		6.5	4	13.79	0	1.69	300.0	45.6	4.66	1.82	50.0	10.6
6	x	65	x	130	48.0	72.0	72.6	8.5	4	15.12	0	1.80	390.0	58.9	5.08	1.97	60.0	12.5
6	x	75	x	150	55.6	83.4	84.0	8.5	4	17.52	0	2.05	609.0	92.3	5.89	2.30	81.2	16.9
6	x	100	x	200	74.8	●	112.0	●	10	23.60	0	2.65	1490.0	225.0	7.94	3.09	149.0	30.6
8	x	100	x	200	98.4	●	148.0	●	10	31.00	0	2.73	1910.0	290.0	7.85	3.06	191.0	39.9
9	x	75	x	150	81.2	122.0	122.0	8.5	6	25.54	0	2.16	850.0	129.0	5.77	2.25	113.0	24.2
10	x	100	x	200	121.0	●	182.0	●	10	38.22	0	2.81	2310.0	351.0	7.77	3.03	231.0	48.8

●…溶接品

※重量を表記しているサイズは即納品です。